



PFT MULTIMIX

The multi-component mixer for the professional

Functionla description

The powerful multi-component mixer PFT MULTIMIX for special mixtures. The material to be mixed is put directly into the container and processed with the specified quantity of water. A homogenous mortar mix is time-saving achieved by strong mixing paddles. The wet mortar is quickly and cleanly drained off with the aid of a flat slide. The PFT MULTIMIX passes the well-mixed and pump-able material on to a PFT conveying pump which conveys it to the application site. The thoroughly developed construction allows a great variety of applications.

Fields of application

- ▶ Concrete restoration
- ▶ Powder adhesives
- ▶ PCC- and SPCC-mortars
- ▶ Mineral plasters
- ▶ Fine-grained concrete
- ▶ Acoustic plasters
- ▶ Floor screeds
- ▶ Synthetic resin plasters
- ▶ Stove setting
- ▶ Epoxy resins
- ▶ Kaminbau
- ▶ Granulates
- ▶ Clay plasters

Advantages at a glance

- ▶ exact mixture ratio of the individual components
- ▶ adding binders
- ▶ intensive and homogeneous processing of the material
- ▶ observation of the material-relevant swelling time
- ▶ fast and thorough mixing due to counteracting mixer arms
- ▶ compact and stable design
- ▶ height adjustable
- ▶ can be combined with conveying pumps
- ▶ simple handling
- ▶ quick and clean draining
- ▶ easy to maintain
- ▶ removeable wear plate
- ▶ flushfloor material outlet



MADE IN GERMANY

All rights and technical changes reserved. We provide guarantee as far as faultless and proper finishing of our machines is concerned. Figures given in relation to output, equipment and performance are based on experience and can vary in case of changing circumstances. Furthermore, the instructions of the material/mortar manufacturers must be observed. Alterations, reprints and photomechanical reproductions, even in extracts, require the permission of Knauf PFT GmbH & Co. KG.

PFT MULTIMIX-GB/10.12/PFT



Knauf PFT

Technical Hotline:

▶ +49 9323 31-1818

▶ Phone +49 9323 31-760

▶ Fax +49 9323 31-770

▶ info@pft-iphofen.de

▶ www.pft.eu

Technical data

PFT MULTIMIX

Basic equipment

Part no.	00 25 16 36
Motor achievement	Drive: 2.2 kW Speed: 56 rpm at 50 Hz Three-phase current: 400 V Power supply: 6 A Connection cable: 5 x 2.5 mm ²
Mixing capacity	Mixing container: max. 140 l capacity of container Ready mixture: approx. 80 l depends on material consistency Grain size: max. 8 mm Three-arm mixing technique with Turbo mixing unit
Dimensions and weight	
Dimensions	Total length: 1,000 mm Total width: 1,030 mm Total height: 1,000 – 1,380 mm
Total weight	148 kg

Batch mixer PFT MULTIMIX complete with:

- geared motor 2.2 kW, 400 V, three-phases, 50 Hz, 56 rpm
- with counter-rotating stirring gear for PCC- and SPCC-mortar
- mixing output approx. 80 l/batch
- adjustable height of chassis

Required accessories

Power cable 5 x 2.5 mm², 50 m, CEE cpl. 16 A
Part no. 20 42 33 50

Power cable 5 x 2.5 mm², 25 m, CEE cpl. 16 A
Part no. 20 42 33 60

Knauf PFT GmbH & Co. KG
P.O. Box 60
97343 Iphofen
Einersheimer Straße 53
97346 Iphofen
Germany

Knauf Gips
Dry construction- and Soil-Systems

Knauf AMF
Ceiling Systems

Knauf Bauprodukte
Pro Solutions at Home

Knauf Gips / Marmorit
Plaster and Facade Systems

Knauf Dämmstoffe
Polystyrol Insulating Material

Marbos
Mortar Systems in Civil Engineering

Knauf Insulation
Insulating Material: Rock Wool,
Glass Wool and Wood Wool

Knauf Integral
Gypsum Fibre Technology
for Soil, Wall and Ceiling

Knauf Perlite
AQUAPANEL® Cement Boards,
Perlit

Sakret Bausysteme
Dry Mortar for
New Build and Renovation